

# **i3PROJECTOR** 3303Wi

# **INTERACTIVE PROJECTOR**

The 3300-lumen i3PROJECTOR combines the roles of ultra-short-throw projectors and interactive  $white boards \ in \ one \ multi-purpose, integrated \ system. \ Simple \ and \ straightforward, \ the \ i3PROJECTOR$ 3303Wi is user-friendly and has advanced features for flexible presenting.

Connecting the 3303Wi to a computer, users can operate computer software with the two interactive pens in the same way as a mouse, and can also digitally annotate the projection without the need for an additional interactive whiteboard.

The dual pen operation enables collaborative learning and helps to boost meeting creativity. As it is mounted to the wall above the projection surface, i3PROJECTOR completely eliminates shadows.

# **MAIN FEATURES**

Ultra short-throw projector Compact design Internal mirror: no dust & scratches possible Affordable lamp 3300 lumens WXGA 1280x800

Aspect ratio 16:10

Auto source

Lamp life 5.000hrs (eco mode)

Speaker 10W

DLP technology

Interactive Technology: Infrared digital stylus

Multi-pen: one or two stylus (depending on operations system)

Interactive Area: 80" to 110" diagonal





Model name	i3PROJECTOR 3303Wi
Native Resolution	1280 x 800
Lamp	260W UHP Lamp
Brightness	3300 lumens
Lamp life time (Normal/ Eco)	3500hrs/5000hrs (eco)
Contrast (Typical)	8000:1
Offset Distance Toler- ance	25mm
Lens/Zoom Throw ratio Image size (Di- agonal)	Sealed design, anti-dust, anti-scratch TR 0.27 85" - 115"
Color wheel	6 segments
Acoustic Noise	Full mode: 35 ±2dB(A), Eco mode: 30 ±2dB(A)
Operation Temperature	For 0 2500 ft, 5 40 °C For 2500 5000 ft, 5 35 °C For 5000 10000 ft, 5 30 °C
Input	VGA X 1 - Audio Jack X 1 - Composite Video X 1 - Composite Audio X 1 HDMI X 2 - Microphone X 1 - RS-232C X 1 - Mini USB-B X 1 - RJ45 X 1 USB-A X 1 - Power X 1
Output	VGA X 1 - Phone Jack X 1(for interactivity) - Audio Jack X 1
No. of Colors	1.07B
Speaker	10W x1
Focus	Manual focus
OSD Languages	18 (English / German / French / Italian / Spanish / Polish / Swedish / Dutch / Portuguese / Japanese / Traditional Chinese / Simplified Chinese / Korean / Russian / Arabic / Norse /Turkish
Power Supply	Universal AC 100 – 240 V ~ 50-60 Hz with PFC input
Power consumption	320W (normal) - 270W (eco)
Standby Power	< 0.5W
Remote Control	IR
Dimension	Length x Width x Height = 383mm x 308mm x 86mm
Weight	5.5kg (12.1lb)



Exclusive design by i3-Technologies - subject to change

#### **ACCESSORIES**

Power cord	1	1.8m
VGA cable	1	1.8m
Remote Control	1	Card type, with battery
Documentation	1	User manual in 18 languages
IR stylus	2	
USB cable	1	1,8 m
Wall mount	1	

Without lens cap, without soft case

### INTERACTIVITY

Interactive Technology: Infrared digital stylus
Interactive Area: 80" to 110" diagonal
Multi-stylus: one or two stylus (depending on operations system)
Interactive Connectivity: USB cable necessary

#### WARRANTY

Projectors 3 years Lamp 6 months, max. 1000 hrs

# **AUTHORISED DISTRIBUTOR**

